

INSTALLATION MANUAL

45903

Level of Difficulty

Easy

Weight Capacity: 2" Ball

Gross trailer weight (GTW) 8,000 lbs.

Weight Capacity: 2-5/16" Ball

Gross trailer weight (GTW) 10,000 lbs.

Parts List

1	Channel mount
1	Dual ball
1	Channel pin
1	Channel clip
1	Hitch pin & clip

Step 1

Insert the adjustable channel mount into the vehicle's trailer hitch receiver tube and secure with the provided hitch pin & clip or hitch lock (hitch lock sold separately).

Step 2

Determine the tow height needed for your towing situation. Raise or lower the dual ball to the desired height and insert the provided channel pin through the dual ball and adjustable channel mount. Secure the pin with the provided channel clip.

WARNING

The provided pin is specifically engineered for this system. If a replacement pin is needed, it must be replaced with an original factory mount pin.

WARNING

Never exceed the vehicle manufacturer's recommended towing capacity. The ratings of the channel-mount system are intended to represent the capability of the product and in no way reflect the ratings or capacity of the towing system it is being used with. The consumer or operator are strongly advised to know the ratings of the various components of the towing system and never exceed the limits of the lowest rated component being used.

Use of any pin other than what is provided by the manufacturer could be a serious safety hazard and will void the warranty.

Never hook up trailer safety chains to the mount system. Ensure the safety chains operate freely around the mount system and do not become entangled.

Product Photo



NOTICE

Before you begin installation, read all instructions thoroughly.

Proper tools will improve the quality of installation and reduce the time required.

Product Registration and Warranty

CURT Group stands behind our products with industry-leading warranties.

Provide feedback and help us to improve our products by registering your purchase at: warranty.curtgroup.com/surveys