



WF-8700 Series Power Centers

Item	Specifications			
Model Number	WF-8712P	WF-8725P	WF-8735P	WF-8740P
Power Consumption	163 W	340 W	600 W	656 W
Input Voltage	105 VAC-130 VAC, 60 Hz			
Output Current	12 A	25 A	35 A	40 A
Converter Type	Three-Stage Converter/Charger			
Voltage Output	13.2-14.4 Vdc range			
Absorption Mode	13.6 Vdc range (nominal voltage)			
Bulk Mode	14.4 Vdc range (quick charging voltage)			
Float Mode	13.2 Vdc range (trickle charge voltage)			

Installation			
AC Circuits	4 ("Main" and 3 branch circuits)		6 ("Main" and 5 branch circuits)
DC Circuits	4 (includes one battery circuit)		6 (includes one battery circuit)
Case Material	Plastic		

Safety Features/Protections			
Over Current	Yes		Yes
Over Temperature	Yes		Yes
Over Voltage	Yes		Yes
Reverse Polarity	Yes		Yes
Short Circuit	Yes		Yes
Cooling Fan	No	Yes	Yes

Shipping			
Dimensions	14.9" x 7.3" x 5"		11.9" x 8" x 5"
Weight	4.5 lbs.	4.75 lbs.	5.5 lbs.

Standards				
Complies with FCC	Yes	Yes	Yes	Yes



WF-8735/40P



WF-8712/25P

Specifications are subject to change without notice or obligation.

www.wfcoelectronics.com