



DIMENSIONS DEPICT OVERALL FINISHED ASSEMBLY. FOR DETAILED DIMENSIONS SEE SHROUD TOP DRAWING 6749A350 AND SHROUD BOTTOM DRAWING 6707A336.

- J JOIN SEAM FROM OUTSIDE AND INSIDE WITH A MIXTURE OF 50% TETRAHYDRAFLURANE AND 50% METHYLETHYLKETONE APPLIED WITH HYPODERMIC SYRINGE. NOT LESS THAN 15 MINUTES LATER, FILL VOIDS WITH A MIXTURE OF 3 POUNDS REGROUND PLASTIC DISSOLVED IN 3/4 GALLON OF 50% THF AND 50% MEK.
- M U.L. RECOGNIZED 94HB ABS EXTRUDED PLASTIC SHEET WITH OVERLAY OF KORAD HC/SM (ON TEXTURED SIDE OF SHEET). COLOR ARCTIC WHITE. KORAD COLOR NUMBER: 65096. FINISHED MATERIAL THICKNESS MUST BE AT OR OVER U.L. RECOGNIZED MINIMUM THICKNESS

VENDOR MUST ISSUE ANNUAL CERTIFICATION LETTER (OR UPON CHANGE OF MATERIAL) STATING RVP PART NO. AND MATERIAL MANUFACTURER & DESIGNATION.

REF. DWG.	UNLESS OTHERWISE SPECIFIED		MATERIAL
	DIMENSION CODE		
TOLERANCES DECIMAL	A DIM. TO TANGENT POINT	F FLUSH WITHIN	M FINISH SPEC. HAIRCELL TEXTURE (OUTSIDE ONLY) NAME SHROUD ASSEMBLY
.x ± .1	B DIM. TO INSIDE MOLD LINE	S SPOTWELD	
.xx ± .05	C DIM. TO OUTSIDE MOLD LINE	BEND RADIUS - SCALE PRINT	
.xxx ± .025			
ANGULAR ±			
FRACTIONAL ±			
ALL DIMENSIONS IN INCHES - DO NOT SCALE PRINT			

FINISH SPEC. HAIRCELL TEXTURE (OUTSIDE ONLY)
NAME SHROUD ASSEMBLY