



LIPPERT COMPONENTS

**ELECTRIC BEDROOM SLIDEOUT SYSTEM
OPERATION AND SERVICE MANUAL**






TABLE OF CONTENTS

SYSTEM	4
Warning	4
Description	4
Prior to Operation	5
System Maintenance	5
OPERATION	6
Warning	6
Extending Slideout Room	6
Retracting Slideout Room	6
Manual Operation	7
SERVICE	9
Adjustment Instructions	9
System Components	10
Troubleshooting	12
Wiring Diagram	15
Ordering Parts	16

SYSTEM

WARNING

FAILURE TO ACT IN ACCORDANCE WITH THE FOLLOWING MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH.

The *Lippert Electric Bedroom Slideout System* is intended for the sole purpose of extending and retracting the slideout room. Its function should not be used for any other purpose or reason than to actuate the slideout room. To use the system for any reason other than what it is designed for may result in damage to the coach and/or cause serious injury or even death.

Before actuating the system, please keep these things in mind:

- 1. Parking locations should be clear of obstructions that may cause damage when the slideout room is actuated.**
- 2. Be sure all persons are clear of the coach prior to the slideout room actuation.**
- 3. Keep hands and other body parts away from slideout mechanisms during actuation. Severe injury or death may result.**
- 4. To optimize slideout actuation, park coach on solid and level ground.**

Description

The *Lippert Electric Bedroom Slideout System* is a belt and pinion gear system, utilizing an electric ball screw actuator to move the room assembly. The motor drives the ball screw in a forward and backward motion to drive the slide room in and out. The actuator comes equipped with an automatic clutching system. The *Lippert Electric Bedroom Slideout System* is designed to operate as a negative ground system.

PRIOR TO OPERATION

Prior to operating the *Lippert Electric Bedroom Slideout System*, follow these four (4) guidelines:

1. Coach should be parked on the most level surface available.
2. Leveling or stabilizing system should be actuated to ensure coach will not move during operation of Bed Lift System.
3. Be sure battery is fully charged.
4. Be sure to keep all persons and pets clear of Bed Lift System during operation.

SYSTEM MAINTENANCE

The *Lippert Electric Bedroom Slideout System* has been static tested to over 2,500 continuous cycles with out any noticeable wear to rotating or sliding parts. It is recommended that when operating in harsh environments (road salt, ice build up, etc.) the moving parts be kept clean and can be washed with mild soap and water. No grease or lubrication is necessary and in some situations may be detrimental to the environment and long term dependability of the system.

Electrical System Maintenance

For optimum performance, the slide-out system requires full battery current and voltage. The battery must be maintained at full capacity. Other than good battery maintenance, check the terminals and other connections at the battery, the control switch, and the electric actuator motor for corrosion, and loose or damaged terminals. Check motor leads under the trailer chassis. Since these connections are subject to damage from road debris, be sure they are in good condition.

NOTE: The *Lippert Electric Bedroom Slideout System* is designed to operate as a negative ground system. A negative ground system utilizes the chassis frame as a ground and an independent ground wire back to battery is necessary (see page 15 for wiring diagram). It is important that the electrical components have good wire to chassis contact. To ensure the best possible ground, a star washer should be used. Over 90% of a unit's electrical problems are due to bad ground connections.

Mechanical Maintenance

Although the system is designed to be almost maintenance free, actuate the room once or twice a month to keep the seals and internal moving parts lubricated.

Check for any visible signs of external damage after and before movement of the travel trailer.

NOTE: *For long-term storage: It is recommend that the room be closed (retracted).*

OPERATION

WARNING

FAILURE TO ACT IN ACCORDANCE WITH THE FOLLOWING MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH.

ALWAYS MAKE SURE THAT THE SLIDEOUT ROOM PATH IS CLEAR OF PEOPLE AND OBJECTS BEFORE AND DURING OPERATION OF THE SLIDEOUT ROOM.

ALWAYS KEEP AWAY FROM THE SLIDE RAILS WHEN THE ROOM IS BEING OPERATED. THE GEAR ASSEMBLY MAY PINCH OR CATCH ON LOOSE CLOTHING CAUSING PERSONAL INJURY.

INSTALL TRANSIT BARS (IF SO EQUIPPED) ON THE SLIDEOUT ROOM DURING STORAGE AND TRANSPORTATION.

EXTENDING SLIDEOUT ROOM

1. Level the unit.
2. Verify the battery is fully charged and hooked-up to the electrical system.
3. Remove the transit bars (if so equipped).
4. Press and hold the IN/OUT switch (Fig. 1B) in the OUT position until the room is fully extended and stops moving.
5. Release the switch, which will lock the room into position.

NOTE: If the slideout switch is held after the room is fully extended, the control will sense that the room has stopped and will shut off the motor after a few seconds.

RETRACTING SLIDEOUT ROOM

1. Verify the battery is fully charged and hooked-up to the electrical system.
2. Press and hold the IN/OUT switch (Fig. 1C) in the IN position until the room is fully retracted and stops moving.
3. Release the switch, which will lock the room into position.

NOTE: If the slideout switch is held after the room is fully retracted, the control will sense that the room has stopped and will shut off the motor after a few seconds.

4. Install the transit bars (if so equipped).




Fig.1

MANUAL OPERATION

WARNING!


Always disconnect battery from system prior to manually operating system. Failure to disconnect battery can cause electricity to backfeed through the motor and cause serious damage to the system as well as void the warranty.

The Lippert Electric slide comes with a manual over ride system. Locate the motor assembly under the bed frame. Locate the drive gear box, Fig. 3 ,page 7. The Manual Override coupler extends from the device gear box and accepts a 3/4" wrench, socket or lug. The coupler is held in place by a hitch pin. Simply take the wrench, ratchet or drill with a nut driver and rotate it clockwise to retract and counterclockwise to extend slide-out. It is important to note that you **DO NOT** need to attempt to disengage the motor as the actuator is "manual ready" Just hook up and crank.

WARNING!

The gears can be stripped out if the room is manually retracted/extended to it's fullest extent and the operator continues to rotate manual override. Any damage due to misuse of the Manual Override feature will disqualify any and all claims to the Limited Warranty.

MANUAL OPERATION



SERVICE

MECHANICAL ROOM ADJUSTMENT

NOTE: All slideout room adjustments must be performed by certified service technicians. Adjustments made by non-certified persons may void any and all warranty claims.

1. Retract room completely.
2. Loosen hex bolts on Alignment Plates (Fig. 4A,).
3. Place jaws of adjustable wrench on Drive Tube (Fig. 4B,).
4. Rotate drive tube until both sides of slide room are sealed in unit.
5. Tighten Adjustment Plate bolts.






Fig.4

(SECOND BOLT NOT SHOWN)

Fig.5



ITEM NO.	PART NUMBER	QTY
1	BASE ASSEMBLY	1
2	RH ARM	1
3	LH ARM	1
4	TROLLEY ASSEMBLY	2
5	MOTOR ASSEMBLY	1
6	OUTER DRIVE TUBE	2
7	INNER DRIVE TUBE	1
8	INNER DRIVE TUBE WITH ADJUSTMENT PLATE	1



BEDROOM SLIDEOUT



LIPPERT COMPONENTS, INC.

TROUBLESHOOTING

The *Lippert Electric Bedroom Slideout System* is only one of four interrelated slideout room system components. These four components are: chassis, room, coach, and *Lippert Electric Bedroom Slideout System*. Each one needs to function correctly with the others or misalignment problems will occur.

Every travel trailer has its own personality and what may work to fix one trailer may not work on another even if the symptoms appear to be the same.

When something restricts room travel, system performance will be unpredictable. It is very important that slide tubes be free of contamination and allowed to travel full distance (Stroke). Ice or mud buildup during travel is an example of some types of contamination that can occur.

When you begin to troubleshoot the system, make sure the battery is fully charged, there are no visible signs of external damage to the actuator or motor and that the motor is wired correctly and all connections are secure.

During troubleshooting, remember that if you change something, that change may affect something else. Be sure any changes you make will not create a new problem.

**You can obtain additional information on the
Lippert Electric Slideout System
by calling 866-524-7821.**

System Troubleshooting Chart

The following troubleshooting chart outlines some common problems, their causes and possible corrective actions. When reference is made to "Power Unit" it is referring to the motor and actuator as a complete assembly. All Power Units are shipped from the factory with a serial number and date code, which should be given to the service technician when asking for assistance.

ROOM DOESN'T MOVE WHEN SWITCH IS PRESSED

<u>Probable cause</u>	<u>Corrective action</u>
Restrictions both inside and out side unit.	Check for and clear restriction.
Low battery voltage, blown fuse, defective wiring.	Check battery. Charge battery or add auxiliary power source. Check battery terminals, and all other wiring. Look for loose/corroded connectors.
Power unit not functioning.	See "Troubleshooting" on page 5.

POWER UNIT RUNS, BUT ROOM DOES NOT MOVE

Actuator not attached to front mounting drive bracket.	Check jam nuts/nylock nuts. Be sure that they are properly tightened and adjusted.
Bad motor or gear housing.	Replace motor.

POWER UNIT RUNS, BUT ROOM MOVES SLOWLY

Low battery, poor ground, extremely low outdoor temperature.	Charge battery, and check ground wire.
Room is in a bind.	Check to see that room is properly adjusted

ROOM STALLS IN MID TRAVEL

Actuator in a bind.	Crank manual override and move room short distance then retry electric switch to move room.
Bad actuator.	Replace actuator if above instructions do not work.

NOTES:

- If the slideout room will not retract there is a manual override that is located on the opposite side of the slideout room. A crank handle is provided with your unit. Once you have the room in the closed position take you unit to the closest dealer. See pages 8 & 9.
- Switch related problems
 - o If room moves opposite from what the switch plate indicates, reverse the motor wires on back of switch (refer to the wiring diagram). Wire size must be 10 GA. Minimum.
 - o If you find that you have a stripped gear, replace the gear pack.
 - o If the room is out of time / synchronization, refer to pages 10 & 13.

TROUBLESHOOTING – MOTOR

Before attempting to troubleshoot the Motor, make sure an adequate power source is available. The unit batteries should be fully charged or the unit should be plugged into to A/C service with batteries installed. Do not attempt to troubleshoot the Motor without assuring a full 12V DC charge

The following tests require only a DC voltmeter (or DC test light) and a jumper lead.

Step 1 - Attach voltmeter (or test light) leads to the negative and positive switch terminals on back of wall switch (See Fig. 6). Does the meter indicate 12V DC?

If **YES**, see **Step 2**; if **NO** see **Step 3**.

Step 2 - If **YES**, at the motor, check the incoming leads to 12V DC (if necessary, disconnect leads at wire splices). Does meter indicate 12V DC? If **YES**, Motor needs to be replaced. The motor is not field serviceable. DO NOT ATTEMPT TO REPAIR. If **NO**, Inspect all wires and connections between the wall switch and the motor. Repair connections as necessary. Recheck as in **Step 1**.


Step 3 - If **NO**, Inspect all connections between battery and switch. Inspect 30A Auto-reset Circuit Breaker (See Fig. 6 for location). Recheck as above in **Step 1**.

Since there are no field serviceable parts in the motor, electrical troubleshooting and service is limited to replacing only those components as previously outlined.

Thorough inspection of wiring and connections is the only other electrical service that can be performed.

WIRING DIAGRAM

Fig.6



ORDERING PARTS

To assist the customer service when ordering parts, please provide the following information:

1. Your Name
2. Company Name
3. Phone Number
4. Shipping Address
5. Billing Address
6. Purchase Order Number
7. Coach
 - A. Serial # and/or VIN #
 - B. Make
 - C. Model
8. Part Number
9. Description
10. Quantity

Please take your coach to an authorized service center for repairs. Systems that have been modified, adjusted, repaired or augmented by a party other than an authorized service center may void any warranty claim with Lippert Components, Inc.