



## TELESCOPING RV FLAGPOLE INSTRUCTIONS

### PARTS LIST:

- Chrome Ball Top
- (4) Swivel Flag Clips
- Black Foam/Rubber Shipping Donut
- (3) "Quick Release Pins" for PNH – 22 Deluxe or (2) "Quick Release Pins" for PNH – 16 Deluxe
- Pole

### ASSEMBLY STEPS:

- # 1 Remove Ball Top, and Foam/Rubber Donut. (NOTE: The foam/rubber donut is just for shipping and storage.)
- # 2 Extend the smallest section of pole first. Secure the pole sections together by pulling and twisting as hard as you can until it will not twist. (NOTE: The upper sections are held together only by friction and the lower sections have pins.)
- # 3 Place (3) of the (4) Flag Clip Rings onto the pole (C, A, A) leaving the smallest ring (B) to be placed onto the shaft of the Chrome Ball.
- # 4 Insert the Chrome Ball into the top of the Pole. (NOTE: if it is too loose, wrap some Duct Tape around the Ball Stem before inserting into the Pole.)
- # 5 Extend the remaining top pole sections the same as earlier in Step #2 (NOTE: Do not tighten the lower pole sections that use Pins)
- # 6 Bottom pole sections use the Pins to keep the pole up so pull the section to where the Pin Holes can be seen. Insert the Pins through the Pole.
- # 7 To collapse pole: Remove Pins, hold pole vertical and hit the bottom section on the ground firmly. It may take several attempts depending on how tightly the upper sections were extended.

### Safety

Never use flagpole near overhead power lines.  
Please use common sense when flying flagpole in high wind conditions.