



Honda CR-V  
Honda Element




**BOLT TORQUE SPECIFICATIONS**

| STANDARD BOLTS: |       |            | METRIC BOLTS: |            |
|-----------------|-------|------------|---------------|------------|
| Size            | Grade | Torque     | Size          | Torque     |
| 5/16"           | 5     | 20 ft/lbs. | 8mm           | 22 ft/lbs. |
| 3/8"            | 5     | 35 ft/lbs. | 10mm          | 42 ft/lbs. |
| 7/16"           | 5     | 56 ft/lbs. | 12mm          | 70 ft/lbs. |
| 1/2"            | 5     | 85 ft/lbs. | 14mm          | 95 ft/lbs. |

# BASE PLATE

Pin Height - 19-1/2" Pin Centers - 22-1/2"



**9518135 PARTS LIST**

| REF. NO. | PART NO. | QTY. | DESCRIPTION                  |
|----------|----------|------|------------------------------|
| 1.       | 00083    | 2    | 1/2"-13UNC Hex Nut           |
| 2.       | 00084    | 2    | 1/2" Lock Washer             |
| 3.       | 01897    | 2    | 1/2"-13UNC x 3-1/2" Hex Bolt |
| 4.       | 07286    | 6    | 8mm Lock Washer              |
| 5.       | 07479    | 6    | 8mm-1.25 x 25mm Hex Bolt     |
| 6.       | 07908-95 | 2    | Heavy Frame Washer           |
| 7.       | 09228    | 6    | 8mm Fender Washer            |
| 8.       | 10689-95 | 2    | Spacer Bushing               |
| 9.       | 13121-35 | 1    | Base Plate Crossmember       |
| 10.      | 5937     | 1    | Plug Mount Kit               |
| 11.      | 12329    | 1    | Loctite (not shown)          |

Please order replacement parts by PART NO. and DESCRIPTION.

ASSEMBLY  
OPERATION  
REPLACEMENT PARTS

**READ** complete manual CAREFULLY  
BEFORE attempting operation.

Doing Our Best to Provide You the Best

# DEMCO PRODUCTS ORIGINAL PURCHASERS LIMITED WARRANTY

## 1. Extent and Duration of this Warranty:

Your Demco product has a Lifetime Limited warranty to be free from defects in materials and workmanship under normal use and service from date of purchase by the original (first) retail owner, or until it is resold or transferred by the original owner. Any part of the Demco product found in the judgment of the manufacturer to be defective in materials or workmanship will be repaired or replaced at the manufacturer's option without charge for parts or labor to the original owner.

## 2. Manufacturer and Warrantor:

Demco  
4010 320th Street  
P.O. Box 189  
Boyden, IA 51234  
(712) 725-2311

## 3. Repair or Replacement Procedure:

If your Demco product develops a defect during the warranty period, promptly notify Demco customer service department. Until such notice is received, Warrantor will not be responsible for any repair or replacement.

Upon receipt of notice from you, Warrantor will have a choice of options in replacing any part it determines to be defective:

- a) Warrantor may require you at your own expense to deliver or ship the part to its factory or authorized dealer. Any defective part will be repaired or replaced and returned to you free of charge. Any part returned to Warrantor and found not to be defective will be returned to you freight collect with an explanation.
- b) Warrantor may elect to ship a new part to its dealer to be exchanged free of charge for the defective part returned by you to the dealer.
- c) Warrantor may elect to ship or deliver a replacement part to your address.

## 4. Limitations on Warranty Coverage:

Coverage under this warranty will be valid only if the customer warranty card is returned by the original purchaser within 30 days of purchase.

Coverage under this warranty will be effective only when a copy of the original invoice, showing the date and location of purchase, accompanies any claim for warranty. This warranty is limited to the original owner and is NON TRANSFERABLE to a second party.

Warrantor has no liability whatsoever and this warranty is null and void if any Demco product has been misassembled or subjected to neglect, negligence, misuse, accident or operated in any way contrary to the operating and maintenance instructions as specified in the Demco Owner's Manual for that model.

This warranty does not cover any product that has been altered or modified so as to affect its operation, performance or durability, or that has been modified to change the intended use of the product.

In addition, the warranty does not extend to repairs made necessary by normal use of parts, accessories or other equipment which in the judgment of Warrantor, are either incompatible with the Demco product, or affect its operation, performance or durability.

This warranty does not cover:

- 1) normal wear and tear
- 2) road film or gravel damage to paint
- 3) paint
- 4) rust damage

Warrantor has a policy of continuous product improvement. We reserve the right to change or improve the design of any Demco product, including but not limited to state of the art changes, without assuming any obligation to modify any product previously manufactured.

Warrantor assumes no responsibility to the owner for loss of use of the product, loss of time, inconvenience or other damage consequential or otherwise, including, but not limited to expense for gasoline, expense of transporting the product to the dealer and expense of returning the product, mechanic's travel time, telephone or telegram charges, road service/towing charges, rental of another product during the time warranty repairs are being performed, travel, lodging, loss or damage to personal property or loss of revenue or earnings.

## 5. Limitations of Implied Warranties:

All implied warranties, if any, expire and terminate upon expiration of this warranty. Some states do not allow limitation on how long an implied warranty lasts, so this limitation may not apply to you.

## 6. Limitation of Consequential Damages:

Warrantor's responsibility under this warranty extends solely to repair or replacement of your Demco product and its component parts.

Warrantor does not assume responsibility for, nor shall it be liable for, any special, incidental or consequential damages. Some states do not allow the exclusion or limitation on incidental or consequential damages, so the above exclusion or limitation may not apply to you.

## 7. Purchaser's Rights:

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

## 8. Exclusive Warranty:

This is the only express warranty made by Demco on your Demco product and no agent, employee, or other person is allowed to change or add to this warranty.

**WARNING: FAILURE TO FOLLOW THESE INSTRUCTIONS CAN RESULT IN LOSS OF TOWING VEHICLE CONTROL, SEPARATION OF THE TOW BAR FROM THE TOWING VEHICLE, SEPARATION OF THE TOWED VEHICLE FROM THE TOW BAR, CAUSING SEVERE PERSONAL INJURY, DEATH, OR PROPERTY DAMAGE.**

## CAUTION

Safety is of utmost importance at all times. There are several items that must be checked each time before using and while using a tow bar.

Before allowing anyone to hook up or operate a tow bar, be sure they have read and understand the proper operating procedure.

**DO NOT** use worn or damaged cables and/or pins.

Be sure the **SAFETY CABLES** are hooked, chassis to chassis, to both the towing and towed vehicles using the crisscross method.

Check clearance between vehicles in a turning situation.

Check base plate mounting bolts for tightness and frame for metal fatigue.

Do not load the towed vehicle with anything as you may exceed the towing capacity of the tow bar.

Keep fingers away from pivot points to prevent personal injury.


Be sure the steering components of the towed vehicle are properly aligned.

**NOTE:** This unit can be backed up in moderate increments. Any severe backwards cornering could result in damage to the Tow Bar and/or towed vehicle chassis.

**For automatic transmissions:** Consult your vehicle owners manual for towing suitability with the drive shaft connected. Otherwise, the towed vehicle will have to be equipped with a transmission pump or drive shaft disconnect.

Check to make sure that all lights are in proper working order.

**The information on towability of vehicles is reprinted with permission of MotorHome® Magazine**, and is believed to be reliable. However, **Demco does not** warrant the information to be correct. Always consult your towed vehicle owner's manual and follow towing instructions. Each year, **MotorHome® Magazine**, compiles a list of vehicles that can be towed four-down behind a motorhome with no modifications required. This guide contains only those vehicles that have been approved by their manufacturers for towing. **This list is enclosed with this manual.**

 **Caution: MotorHome® Magazine** left out any vehicles that have towing speed limits slower than 55 m.p.h., or distance limits of less than 200 miles. At a minimum, these vehicles require significant modification, such as the use of an aftermarket product, to make them towable. The availability of a **Demco Tow Bar Base Plate does not** imply that these vehicles can be modified or that there is an aftermarket product available. Refer to your vehicle owner's manual or consult your dealer to determine whether your vehicle can be modified to make it towable. Failure to observe this precaution could result in property damage or personal injury.

## IMPORTANT INSTALLATION ITEMS


DEMCO products and accessories are intended to be installed by professional installers with experience, proper equipment and the ability to do modification work. Installers with these qualifications can be found in RV and Automotive Service Centers.

If the car to be towed has been in an accident, the chassis may be damaged in an area where the Base Plate attaches. It may no longer be suitable for towing. Extreme caution and careful examination are required in such a situation. It is also likely, even from a minor accident, that the hole alignment will be more difficult due to hole alignment problems.

Many DEMCO Base Plates are designed to use existing holes and hardware to mount the Base Plate to the towed vehicle. Even though the bolt is there, however, do not assume it is adequate for mounting the Base Plate. Manufacturers make many changes in hardware both within and between model years. Be sure the bolt is long enough to protrude past the nut a distance no less than 1/2 the diameter of the bolt, after the Base Plate is mounted. The threads should be in good condition. **We require that "LOCTITE® Blue" be used on all bolts.** If a new bolt is required, be sure it is SAE Grade 5 or Metric 8.8.

**NOTE: The dimensional variations between otherwise identical vehicles can be considerable. Some minor modifications may have to be made to ensure a proper fit.**

## '02-03 HONDA CR-V INSTALLATION



1. Open hood and remove six plastic push fasteners from across top of grill and fascia.  
**Note:** Fascia and grill will be removed as a unit.



2. Remove two bolts from each side from bottom of fascia on outside edges and two plastic push fasteners from center, underneath fascia front.



3. Remove one screw from each side, fascia to fender, by going through wheel well.

## 2003 HONDA ELEMENT INSTALLATION



1. Open hood and remove five plastic push fasteners from across top of plastic filler panel.



2. Remove nine plastic push fasteners from the top of grill/fascia. **Note:** Fascia and grill will be removed as a unit.




3. Remove two bolts from each side from bottom of fascia on outside edges and six plastic push fasteners from center, underneath fascia front.

## '02-03 HONDA CR-V INSTALLATION



4. Pull fascia straight out by fender (see picture) and back and off.



5. Remove fascia support tin, four bolts on passenger's side and three bolts on driver's side. This assembly and bolts will not be reused. **NOTE:** Some models may have a temp sensor located on tin support, remove clip and relocate.

## 2003 HONDA ELEMENT INSTALLATION



4. Remove one screw from each side of wheel




5. Pull fascia straight down by fender, and release tab on fascia (see pictures). Carefully pull fascia forward and off.

## '02-'03 HONDA CR-V INSTALLATION




6. Relocate horn on each side, from straight down to outwards. Horn wiring clip will have to be removed from its hole so horn can be loosened and turned according to picture.




7. Install spacer bushing inside frame and hold in place with 1/2" x 3-1/2" bolt and heavy frame washer. **NOTE:** Don't stick 1/2" bolt all the way through so base plate can slide on.

## 2003 HONDA ELEMENT INSTALLATION




6. Remove facia support tin, four bolts on each side. This assembly and bolts will not be reused. **NOTE:** Some models may have a temp sensor located on tin support, remove clip and relocate.




7. Install spacer bushing inside frame and hold in place with 1/2" x 3-1/2" bolt and heavy frame washer. **NOTE:** Don't stick 1/2" bolt all the way through so base plate can slide on.

## '02-'03 HONDA CR-V INSTALLATION




8. Slide base plate on frame horn until the top two bolt holes are lined up on each side.



9. Install two 8mm-1.25 x 25mm bolts, 8mm lock washers and 8mm fender washers on top of each side and one 8mm-1.25 x 25mm bolt, 8mm lock washer and 8mm fender washer on bottom of each side. Do not tighten bolts yet. Put 1/2" bolt all the way through other side of base plate and install 1/2" lock washer and 1/2" hex nut. Tighten 1/2" bolts first then tighten 8mm bolts.  
**NOTE:** Use **LOCTITE** on all bolts and tighten according to bolt chart on front page.

## 2003 HONDA ELEMENT INSTALLATION



8. Slide base plate on frame horn until the top two bolt holes are lined up on each side.



9. Install two 8mm-1.25 x 25mm bolts, 8mm lock washers and 8mm fender washers on top of each side and one 8mm-1.25 x 25mm bolt, 8mm lock washer and 8mm fender washer on bottom of each side. Do not tighten bolts yet. Put 1/2" bolt all the way through other side of base plate and install 1/2" lock washer and 1/2" hex nut. Tighten 1/2" bolts first then tighten 8mm bolts.  
**NOTE:** Use **LOCTITE** on all bolts and tighten according to bolt chart on front page.


## '02-03 HONDA CR-V INSTALLATION



10. Trim outer most lower vertical grill bar to allow clearance for baseplate chain anchor plate.
11. Reinstall fascia and all of its hardware.
12. Plug mount (item #10) may be installed if desired in convenience holes on either chain anchor or as desired.

**NOTE:** Excess material may be trimmed from bracket.

## 2003 HONDA ELEMENT INSTALLATION



10. You may need to bend fascia support tab down for more clearance with the fascia.



11. Trim outer most lower vertical grill bar to allow clearance for baseplate chain anchor plate.
  12. Reinstall fascia and all of its hardware.
  13. Plug mount (item #10) may be installed if desired in convenience holes on either chain anchor or as desired.
- NOTE:** Excess material may be trimmed from bracket.





# Warranty Registration

4010 320th Street • Box 189 • Boyden, Iowa 51234  
Toll Free 800-54DEMCO (800-543-3626) • FAX 800-845-6420  
www.demco-products.com

|        |                       |
|--------|-----------------------|
| Ag     | <input type="radio"/> |
| RV     | <input type="radio"/> |
| Rental | <input type="radio"/> |
| Brakes | <input type="radio"/> |
| Marine | <input type="radio"/> |

|  | Very Satisfied               | Satisfied                   | Dissatisfied          | Very Dissatisfied     |
|--|------------------------------|-----------------------------|-----------------------|-----------------------|
| How satisfied are you with our product?  | <input type="radio"/>        | <input type="radio"/>       | <input type="radio"/> | <input type="radio"/> |
| How satisfied are you with the dealership/distributor sales staff?<br>Dealer/Distributor Name _____ City _____ State _____             | <input type="radio"/>        | <input type="radio"/>       | <input type="radio"/> | <input type="radio"/> |
| How satisfied are you with the company sales staff?  | <input type="radio"/>        | <input type="radio"/>       | <input type="radio"/> | <input type="radio"/> |
| How satisfied are you with the delivery?   | <input type="radio"/>        | <input type="radio"/>       | <input type="radio"/> | <input type="radio"/> |
| Did you have any contact with a Demco Representative?<br>If <b>YES</b> , how satisfied were you?                                       | YES<br><input type="radio"/> | NO<br><input type="radio"/> | <input type="radio"/> | <input type="radio"/> |
| I would recommend this product to my family and friends.   | YES                          | NO                          |                       |                       |
| Would you purchase again from DEMCO?   | YES                          | NO                          |                       |                       |
| Since taking delivery, have you been contacted by the dealer?  | YES                          | NO                          |                       |                       |
| Did you have any problems with this DEMCO product?<br>If <b>YES</b> , are you satisfied with the company's resolution of your problem? | YES<br><input type="radio"/> | NO<br><input type="radio"/> | <input type="radio"/> | <input type="radio"/> |

Please list the specific source of information prompting this purchase.

\_\_\_\_\_

\_\_\_\_\_

After purchasing this product, do you see any needed product improvement? \_\_\_\_\_ If yes, what improvement? \_\_\_\_\_

\_\_\_\_\_

What other products would you like to see DEMCO offer? \_\_\_\_\_

\_\_\_\_\_

Comments \_\_\_\_\_

\_\_\_\_\_

Owner's Name: \_\_\_\_\_ Mailing Address: \_\_\_\_\_

City: \_\_\_\_\_ State: \_\_\_\_\_ Zip Code: \_\_\_\_\_

Model#: \_\_\_\_\_

Serial #: \_\_\_\_\_

Purchase Date: \_\_\_\_\_

Owner's Signature: \_\_\_\_\_

Please return to DEMCO By FAX or tri-folding this form to the backside, it is pre-addressed.

Postage

*Demco  
4010 320th Street, Box 189  
Boyden, Iowa 51234*

# NOTES



4010 320th St., P.O. BOX 189, BOYDEN, IA. 51234  
PH: (712) 725-2311  
FAX: (712) 725-2380 or 1-800-845-6420  
TOLL FREE: 1-800-54DEMCO (1-800-543-3626)  
[www.demco-products.com](http://www.demco-products.com)