

# SAFETY DATA SHEET

Revision Date 27-Oct-2016 Version 5

# 1. IDENTIFICATION

Product identifier

Product Name 133K ANTI-SEIZE LUBRICANT 8OZ

Other means of identification

Product Code 80078 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Lubricant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufactured and Distributed by:May Also Be Distributed by:ITW PermatexITW Permatex Canada6875 Parkland Blvd.35 Brownridge Road, Unit 1Solon, OH 44139 USAHalton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

### 2. HAZARDS IDENTIFICATION

### Classification

**OSHA Regulatory Status** 

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral Category 4

# Label elements

### **Emergency Overview**

### Warning

Harmful if swallowed



Revision Date 27-Oct-2016

Appearance Silver Physical state Paste Odor Petroleum

### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

#### **Precautionary Statements - Response**

Get medical advice/attention if you feel unwell

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

#### **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

- The classification as a carcinogen 1 need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346. This note applies only to certain complex oil derived substances in Annex I

Unknown acute toxicity 19.23275 % of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
DISTILLATES (PETROLEUM), HYDROTREATED	64742-52-5	30 - 60	*
HEAVY NAPHTHENIC			
ALUMINIUM POWDER	7429-90-5	5 - 10	*
PARAFFIN OILS (PETROLEUM), CATALYTIC	64742-71-8	3 - 7	*
DEWAXED LIGHT			

### 4. FIRST AID MEASURES

#### **Description of first aid measures**

General advice Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

**Skin contact** IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician.

Wash contaminated clothing before reuse.

**Inhalation** IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Call a POISON CENTER or doctor/physician if you feel unwell. Rinse

mouth.

**Self-protection of the first aider** Use personal protective equipment as required.

Revision Date 27-Oct-2016

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

Water.

Specific hazards arising from the chemical

None in particular.

**Explosion data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

Environmental precautions

**Environmental precautions**Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological Information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel

into suitable containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

### 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes or

clothing. Use personal protective equipment as required. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible materials Strong oxidizing agents, Acids, Alkalis, Amines

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

\_\_\_\_\_

#### Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ALUMINIUM POWDER	TWA: 1 mg/m³ respirable fraction	TWA: 15 mg/m³ total dust	TWA: 10 mg/m <sup>3</sup> total dust
7429-90-5		TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 5 mg/m³ respirable dust
		(vacated) TWA: 15 mg/m³ total dust	TWA: 5 mg/m <sup>3</sup> Al
		(vacated) TWA: 5 mg/m³ respirable	
		fraction (vacated) TWA: 5 mg/m <sup>3</sup> Al	
		Aluminum	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

**Eye/face protection** Tight sealing safety goggles.

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

appropriate.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state Paste
Appearance Silver
Odor Petroleum

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No information available
Melting point / freezing point
Boiling point / boiling range No information available
No information available

Flash point > 93 °C / > 200 °F Tag Closed Cup
Evaporation rate < 1 Butyl acetate = 1

Flammability (solid, gas) No information available Flammability Limit in Air

Upper flammability limit: No information available

Lower flammability limit: No information available
Vapor pressure <5 mm Hg

Vapor density >1 Air = 1

Relative density 1.17 Water solubility Negligible

Solubility in other solvents
Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity
No information available

#### 80078 - 133K ANTI-SEIZE LUBRICANT 80Z

**Explosive properties**Oxidizing properties
No information available
No information available

Other Information

Softening pointNo information availableMolecular weightNo information available

VOC Content (%) 0

DensityNo information availableBulk densityNo information available

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions

### Possibility of Hazardous Reactions

None under normal processing.

### Conditions to avoid

Excessive heat.

### Incompatible materials

Strong oxidizing agents, Acids, Alkalis, Amines

### **Hazardous Decomposition Products**

Carbon oxides

### 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

**Inhalation** May cause irritation of respiratory tract.

**Eye contact** Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

**Skin contact** May cause skin irritation and/or dermatitis.

**Ingestion** Harmful if swallowed.

# Information on toxicological effects

**Symptoms** No information available.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization No information available. Germ cell mutagenicity**No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Carcinogenicity	The table bei	The table below indicates whether each agency has listed any ingredient as a carcinogen.		
Chemical Name	ACGIH	IARC	NTP	OSHA
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC 64742-52-5	A2	Group 1	Known	X
PARAFFIN OILS (PETROLEUM), CATALYTIC DEWAXED LIGHT	A2	Group 1	Known	X

\_\_\_\_\_

64742-71-8

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Central Vascular System (CVS), Eyes, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 1978 mg/kg ATEmix (inhalation-vapor) 32255 mg/l

### 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

32.42995 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

### Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

#### **Mobility**

No information available.

### Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ALUMINIUM POWDER	Ignitable powder
7429-90-5	

# 14. TRANSPORT INFORMATION

DOT

Proper shipping name: Not regulated

<u>IATA</u>

Proper shipping name: Not regulated

**IMDG** 

Proper shipping name: Not regulated

### 15. REGULATORY INFORMATION

### **International Inventories**

**TSCA** Complies Complies **DSL/NDSL EINECS/ELINCS** Complies **ENCS** Complies Complies **IECSC** Complies **KECL PICCS** Complies **AICS** Complies

### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

## US Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %		
ALUMINIUM POWDER - 7429-90-5	1.0		
SARA 311/312 Hazard Categories			
Acute health hazard	Yes		
Chronic Health Hazard	No		
Fire hazard	No		
Sudden release of pressure hazard	No		
Reactive Hazard	No		

### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

### **US State Regulations**

### **California Proposition 65**

This product does not contain any Proposition 65 chemicals

### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
CALCIUM OXIDE	X	X	X
1305-78-8			
GRAPHITE	X	X	X
7782-42-5			
ALUMINIUM POWDER	X	X	X
7429-90-5			
PARAFFIN OILS (PETROLEUM),	-	X	-

CATALYTIC DEWAXED LIGHT 64742-71-8			
COPPER 7440-50-8	Х	X	Х

#### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

#### **WHMIS Hazard Class**

D2B - Toxic materials

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 1 Flammability 1 Instability 0

HMIS Health hazards 1 Flammability 1 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 27-Oct-2016

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**